




# BC MARINE TAPE

Bad Weather Cost Money...  
Protect Your Valuable Cargo.



BC Hatch Cover Sealing Tape is composed of PVC backing and a rubberized mastic reinforced by woven polyester. These combine to produce tapes capable of withstanding the harshest conditions while providing a watertight seal. It has various

qualities, sizes and packings to comply with any kinds of requirements.





BC Marine Tape can duly protect your valuable cargo against seawater and withstand the harshest conditions with a watertight seal.

## Characteristics

- Various sizes and packings
- Excellent adhesion
- No remains on removal
- No reheating required
- Medium/Heavy/Super Heavy duty available
- Good adhesion on hot and cold weather

## Usage

- Hatch cover
- Jointed parts
- Cracked coaming



## Sizes/Packings

### Sheet(Strip) Type

### Roll Type

| Width            | Thick.         | Length          | Sheets/box               | IMPA Code | ISSA Code | Width            | Thick.         | Length          | Rolls/box                | IMPA Code | ISSA Code |
|------------------|----------------|-----------------|--------------------------|-----------|-----------|------------------|----------------|-----------------|--------------------------|-----------|-----------|
| <del>70mm</del>  | <del>3mm</del> | <del>1.2m</del> | <del>60sheets(72m)</del> | 23 24 67  | 43 003 09 | <del>70mm</del>  | <del>3mm</del> | <del>24m</del>  | <del>3rls.(72m)</del>    | 23 24 58  | 43 003 18 |
| <del>101mm</del> | <del>3mm</del> | <del>1.2m</del> | <del>40sheets(48m)</del> | 68        | 10        | 101mm            | 3mm            | 24m             | 3rls.(72m)               | 59        | 19        |
| <del>152mm</del> | <del>3mm</del> | <del>1.2m</del> | <del>30sheets(36m)</del> | 69        | 11        | 152mm            | 3mm            | 24m             | 2rls.(48m)               | 60        | 20        |
| <del>70mm</del>  | <del>4mm</del> | <del>1.2m</del> | <del>45sheets(54m)</del> | 23 24 74  | 43 003 12 | <del>70mm</del>  | <del>4mm</del> | <del>18m</del>  | <del>4rls.(72m)</del>    | 23 24 64  | 43 003 21 |
| 101mm            | 4mm            | 1.2m            | 45sheets(54m)            | 75        | 13        | 101mm            | 4mm            | 18m             | 3rls.(54m)               | 65        | 22        |
| 152mm            | 4mm            | 1.2m            | 30sheets(36m)            | 76        | 14        | 152mm            | 4mm            | 18m             | 2rls.(36m)               | 66        | 23        |
| <del>70mm</del>  | <del>3mm</del> | <del>1.2m</del> | <del>40sheets(48m)</del> | 23 24 77  | 43 003 15 | <del>70mm</del>  | <del>4mm</del> | <del>1.2m</del> | <del>40sheets(48m)</del> | 78        | 16        |
| <del>101mm</del> | <del>3mm</del> | <del>1.2m</del> | <del>30sheets(36m)</del> | 78        | 16        | <del>101mm</del> | <del>4mm</del> | <del>1.2m</del> | <del>30sheets(36m)</del> | 79        | 17        |
| <del>152mm</del> | <del>3mm</del> | <del>1.2m</del> | <del>20sheets(24m)</del> | 79        | 17        |                  |                |                 |                          |           |           |



## Application Instruction

- Brush away any foreign materials from the joint surface, and wipe the surface dry.
- Peel off the backing paper and press the tape onto surface.
- Recheck the tape periodically and apply a second tape if any unusual abrasions occur.
- New Application is necessary, peel off the old tape with a deck scraper and apply the new.
- We recommend to leave a thin adhesive-layer of the old mastic on the joint surface to prevent rust and make the next application easier and more effective.



### BC TAEHANG INDUSTRIAL CORP.

640-1, Youngju-Dong, Jung-Gu, Busan, Korea  
Tel: +82-51-442-6191/2 Fax: +82-51-442-6193  
e-mail: info@bcinternational.co.kr  
http://www.bcinternational.co.kr

Distributor